

SPP-L410

4 inch Mobile Label Printer



Ticketing



Healthcare



Logistics



Retail

Compact yet Rugged



Productivity Enhancing Performance

- Fully compatible with market-leading programming languages
- Extensive memory up to 256 MB SDRAM, 512 MB Flash
- Fast data processing and printing speed up to 4 ips (102 mm/sec)
- Supports gap, Black Mark, paper cover open sensor (Fixed Transmissive Sensors)



Reliable Printing on the Move

- Connectivity options including Bluetooth® and Dual-band Wireless Lan (2.4GHz and 5GHz), USB and Serial
- Compatible with all major operating systems including Android™, iOS™ and Windows®
- Supports Easy Bluetooth Pairing™ via embedded NFC tag enabling auto pairing
- Smart Wi-Fi setting via mobile devices



Rugged and Easy to Carry

- Smallest in its class (143x138x66 mm)
- Ergonomic and lightweight (530 g)
- 1.8 m / 6 ft. drop rate
- Resistance to water and dust (IP54)
- Various accessories and connectivity ports

SPP-L410

4 inch Mobile Label Printer

9x
No.1 MOBILE
RECEIPT
PRINTER
MANUFACTURER



Reported by
Chunichisha

Specifications

Printer Specifications

Print Method

Direct Thermal

Print Speed

Up to 4 ips (102 mm/sec - Liner)
Up to 3 ips (76 mm/sec - Linerless)

Print Resolution

203 dpi

Print Width

Up to 104 mm

Sensing

Paper End
Gap
Black Mark
Paper Cover Open

Media Characteristics

Media Type

Liner, Linerless (Optional)

Media Width

112 mm / 105 mm (Optional)

Media Roll Diameter

Up to 56 mm

Media Thickness

0.07 ~ 0.19 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (WxDxH)

143 x 138 x 66 mm
(5.63 x 5.44 x 2.60 inch)

Weight

Including battery: 530 g (1.17 lbs.)
Paper: 242 g (0.53 lbs.)

Electrical

7.3 V Li-ion, 2850 mAh (Nominal),
Rechargeable Charging time: Up to 4 hrs
EnergyStar Certified

Performance Characteristics

Memory

128 MB SDRAM, 256 MB Flash
256 MB SDRAM, 512 MB Flash (Optional)

Interface

Standard: USB V2.0 HS + Serial
Optional: USB V2.0 HS + Serial + Bluetooth / WLAN

WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc,
Wi-Fi Direct, SoftAP)
- WEP40/104, WPA1/2 (PSK, EAP)

Easy Bluetooth Pairing™ via NFC

Environment Characteristics

Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)
Storage: -30 ~ 70°C (-22 ~ 158°F)

Humidity

Operating: 10 ~ 80% RH

Sealing

IP54

Drop Rate

1.8 m (6 ft.)

Software

Emulation

SLCS, BPL-Z™, BPL-C™

Driver / Utility

Windows Driver (Europlus/Seagull),
Linux/Mac CUPS Driver, Virtual COM USB Driver,
Utility Program, Label Artist-II™, Bartender UL,
OPOS/JPOS Driver, SAP® Device Driver,
Network Auto Installer

SDK / Plugin

Android/iOS/Windows SDK, Linux SDK,
Chrome SDK, Xamarin SDK, Cordova Plugin

Application

Label Artist™ Mobile (Android, iOS),
mPrint App (Android, iOS)

Fonts / Graphics / Symbolologies

Fonts

Bitmap Fonts (10 SLCS™, 16 BPL-Z™, 7 BPL-C™),
Scalable Fonts (1 SLCS™, 1 BPL-Z™),
23 Code page,
Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

Graphics

Supporting user-defined fonts, graphics,
formats, layouts and logos

Barcode Symbolologies

1D: Codabar, Code 11, Code 39, Code 93,
Code 128, EAN-13, EAN-8, Industrial 2-of-5,
Interleaved 2-of-5, Logmars, MSI, Plessey,
Postnet, GS1 DataBar (RSS-14),
Standard 2-of-5, UPC/EAN extensions,
UPC-A, UPC-E, IMB
2D: Aztec, Codablock, Code 49, Data Matrix,
MaxiCode, MicroPDF417, PDF417, QR code,
TLC 39

Accessories

Standard Accessories

Belt Clip, Battery, Battery Charger, Power Cord

Optional Accessories

Belt Strap, Shoulder Strap, Single Battery Cradle,
Quad Battery Charger, Vehicle Charger,
Serial/USB Cable,
RAM Mount Vehicle Holder, Case

Supplies

Compatible with B-linerless™ BIXOLON's flexible
and ecological linerless label consumables



BR_SPP-L410_EN_JUN23_V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON
www.BIXOLON.com

BIXOLON Co., Ltd.
+82 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Mexico
+521 55 8852 7880
marcelo@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

BIXOLON MEA
+971 4 222 6480
russell@bixolon.com