

SUNMI D2s PLUS Smart Desktop Terminal

New

Better printing performance, and more.

Powered by
SUNMI OS

A more powerful printer inside.

A desktop terminal that prints at 250mm/s* definitely will be your great helper at peak hours. The 80mm wide receipts give you more room for your creative ideas that show your brand personality, no matter by long texts or images, or combined.

A printer that "feels" smoothes your business operations.

The newly added sensors for paper jam, paper pickup, out of paper and overheated motor can effectively protect the printer and also delivers smooth receipt printing experience.

More configuration options.

Three display options. Find what combination works best for you.



Display Options

15.6"

Single 15.6"FHD,1920*1080

15.6" + 10.1"

Main 15.6"FHD,1920*1080
Secondary 10.1"HD, 1024*600

15.6" + 15.6"

Main 15.6"FHD,1920*1080
Secondary 15.6"FHD,1920*1080





SUNMI D2s PLUS Specs

Model Approved L1584 L1585 L1586	OS Android 11 SUNMI OS	CPU RK 3568 Cortex-A55 Processor 2.0GHz	Memory 2GB RAM+16GB ROM	Speaker 1* 3W
Display Config 1: Main: 15.6" FHD, 1920*1080 Capacitive multi-touch screen Config 2: Main: 15.6" FHD, 1920*1080 Capacitive multi-touch screen Secondary: 10.1" HD, 1024*600 Capacitive multi-touch screen Config 3: Main: 15.6" FHD, 1920*1080 Capacitive multi-touch screen Secondary: 15.6" FHD, 1920*1080 Capacitive multi-touch screen	Printer Built-in 80mm thermal printer Print speed: 250mm/s Service life: 150km Max paper roll diameter: 80mm	Ports 5* USB Type A port 1* RJ11 port 1* RJ12 cash drawer port 1* RJ45 LAN 1* 3.5mm audio jack 1* Power port 1x Micro-USB debug port	Bluetooth Support Bluetooth 5.0 Support BLE	
Ethernet LAN 100M	Button 1* Power (lock screen) key	External Memory Card 1* MicroSD (TF) Up to 1TB	Wi-Fi IEEE 802.11 a/b/g/n/ac 2.4 & 5 GHz dual band	Power Adapter Input: AC100~240V/1.7A Output: DC24V/2.5A
Dimensions (L*W*H) Config 1: 381.73*331.6*498.03mm Config 2: 381.73*349.08*498.52mm Config 3: 381.73*369.61*525.52mm	Weight Config 1: 7.0kg Config 2: 7.770kg Config 3: 8.695kg	Environment Working temp.: 0°C~40°C Storage temp.: -20°C~60°C		

1.The usable memory may be less than the installed memory.
2.All specifications are subject to change without (prior) notice.